



DMD2401L

L-Band VSAT/SCPC Satellite Modem



HIGHLIGHTS

- ▶ Operates in L-Band (950 - 1750 MHz)
- ▶ Light Weight, Low Profile
- ▶ BPSK, QPSK and OQPSK Operation (8PSK Optional)
- ▶ 4.8 to 5000 Kbps
- ▶ One Bit-Per-Second Steps
- ▶ 1/2, 3/4, and 7/8 Rate Viterbi
- ▶ 1/2, 3/4, and 7/8 Rate Sequential (Optional)
- ▶ 0.495 and 0.793 Rate Turbo Product Code (Optional)
- ▶ Accurate E_b/N_0 , Symbol Error Rate and Bit Error Rate Display
- ▶ IBS or IDR Framing (Optional)
- ▶ Drop and Insert (Optional)
- ▶ Automatic Uplink Power Control (AUPC) (Optional)
- ▶ 2/3 Trellis 8PSK (Optional)
- ▶ Ethernet Terrestrial Interface (Optional)

OVERVIEW

The Radyne ComStream DMD2401L L-Band Satellite Modem offers the best features of a sophisticated programmable modem, at an affordable price.

Digital microprocessor control eliminates virtually all on-board adjustments. Direct Digital Synthesis (DDS) of the IF and data rate synthesizers allow settings to one hertz and one bit-per-second, respectively. These features ensure that the modem will perform over years of service without degradation.

The DMD2401L is designed to perform as both ends of a satellite Single Channel Per Carrier (SCPC) link or as the VSAT remote site modem in a TDMA hub system. The

DMD2401L is perfect for mesh or star topology networks. The modulator and demodulator operate independently using BPSK, QPSK, OQPSK or 8PSK (optional) modulation in either SCPC or VSAT modes.

The DMD2401L is also the ideal VSAT modem for use in a point-to-point frame relay hybrid network. Other applications include FDMA, telephony, video conferencing, long distance learning, paging and news gathering.

Selection of any data rate is provided over the following ranges:

- 4.8 Kbps to 1250 Kbps BPSK
- 9.6 Kbps to 4375 Kbps QPSK
- 9.6 Kbps to 4375 Kbps OQPSK
- 64 Kbps to 5000 Kbps 8PSK (Optional)

The DMD2401L is programmable from the front panel. The program menu was specifically designed for ease of use to quickly put the modem online and to input network changes. The modem can also be monitored and controlled through the RS-485 or RS-232 serial control channel.

Available options for the DMD2401L include a low data rate asynchronous serial overhead channel for remote monitor and control. Additionally, a Reed-Solomon or Turbo Product Codec is available for applications requiring Bit Error Rates of 10^{-10} .

All of the configuration, monitor and control functions are available at the front panel. Operating parameters, such as variable data rates, FEC code rate, modulation type, IF frequencies, IBS/IDR framing and interface type can be readily set and changed at the front panel by earth station operations personnel.



DMD2401L L-Band VSAT/SCPC Satellite Modem

SPECIFICATIONS

Transmit and Receive Data Rates

DMD2401L:	BPSK - 4.8 to 1250 Kbps, Rate 1/2 QPSK - 9.6 to 2500 Kbps, Rate 1/2 QPSK - 9.6 to 3750 Kbps, Rate 3/4 QPSK - 9.6 to 4375 Kbps, Rate 7/8 OQPSK - 9.6 to 2500 Kbps, Rate 1/2 OQPSK - 9.6 to 3750 Kbps, Rate 3/4 OQPSK - 9.6 to 4375 Kbps, Rate 7/8 8PSK - 64 to 5000 Kbps, Rate 2/3 (Optional) Selectable in 1 bps Steps
Data Rate Setting:	Selectable in 1 bps Steps

Modulator Specifications

Frequency Range:	950 to 1750 MHz in 1 Hz Steps
Frequency Stability:	±1.0 ppm (±0.1 ppm Optional)
Level Control:	-5 to -30.0 dBm, 0.1 dB Steps
Level Accuracy:	±1.0 dB Over Frequency and Temperature
Impedance:	50 Ohm
Return Loss:	14 dB (Minimum)
Tx On/Off Isolation:	-55 dB
Phase Noise:	100 Hz -63 dBc 1000 Hz -73 dBc 10 kHz -83 dBc 100 kHz -93 dBc
Connector:	Type - SMA

Demodulator Specifications

Frequency Range:	950 - 1750 MHz in 1 Hz Steps
Input Carrier Range:	-65 to -40 dBm (Symbol Rate < 64 kHz) -50 to -30 dBm (Symbol Rate > 640 kHz)
Aggregate Power:	Minimum of -10 dBm or 35 dBc
IF Input Impedance:	50 Ohm
Return Loss:	14 dB (Minimum)
Connector:	Type - SMA
Carrier Acquisition:	±100 kHz in 1 kHz Steps

Typical E_b/N_0 (Viterbi)	Rate 1/2	Rate 3/4	Rate 7/8
@ BER=10 ⁻⁵	5.1	6.2	7.5
@ BER=10 ⁻⁷	6.2	7.7	8.6

Typical E_b/N_0 @ 64 Kbps Sequential (optional)	Rate 1/2	Rate 3/4	Rate 7/8
@ BER=10 ⁻⁵	4.0	5.0	6.1
@ BER=10 ⁻⁷	4.9	5.9	7.4

Typical E_b/N_0 (Trellis 2/3, 8PSK)	Rate 2/3
@ BER=10 ⁻⁵	7.2
@ BER=10 ⁻⁷	8.9

Typical E_b/N_0 (Turbo Product Code)	0.495	0.793
@ BER=10 ⁻⁵	<3.0	3.5
@ BER=10 ⁻⁷	<3.0	3.8

Note: E_b/N_0 typical values include effect of using differential encoding and V.35 scrambler.

Descrambler:	Intelsat V.35, Mode Selectable
Data Buffering:	8 Bits to 262,144 Bits, in 8-Bit Steps

Alarms

Summary Alarms:	Two separate form-C contacts available at the rear panel. Each provides a summary alarm of fault conditions.
-----------------	--

Front Panel LED Indicators

Unit:	Power Alarm Event Remote
Demodulator:	Signal Lock Major Alarm Minor Alarm Test Mode
Modulator:	Transmit On Major Alarm Minor Alarm Test Mode

Monitor and Control

All operating parameters can be monitored and controlled via the front panel display/keypad or the RS485 or RS232 serial control channel in either terminal or command modes. The following modem parameters may be controlled and/or monitored:

Transmit and Receive Frequencies
Transmit and Receive Offsets
Modulator Power Level
Modulator On/Off
Modulator/Demodulator Modulation (BPSK, QPSK, OQPSK or optional 8PSK)
Modulator/Demodulator Data Rates (1 bps Steps)
Modulator/Demodulator Code Rates (1/2, 3/4, 7/8, Optional 0.495 and 0.793 TPC, and 2/3 8PSK)
Modulator/Demodulator Differential Decoders (On/Off)
Modulator/Demodulator Scrambler (On/Off)

Terrestrial Interfaces

T1 (DSX1):	1.544 Mbps, 100 ohm and B8ZS
E1 (G.703):	2.048 Mbps, 75 and 120 ohm, HDB3
ITU V.35:	All Rates, Differential, Clock/Data, DCE
RS-422/-449:	All Rates, Differential, Clock/Data, DCE
Universal Interface:	Optionally Available
Ethernet:	10BaseT RJ-45 optionally available

Options

Turbo Product Codec	A Reed-Solomon Codec is Available
Concatenated Codec:	Asynchronous overhead channel for remote control and order-wire applications.
Asynchronous Channel:	
IDR:	Per IESS 308
IBS:	Per IESS 309
8PSK:	Per IESS 310
Drop and Insert:	(Optional)
Terrestrial Data:	1.544 Mbps or 2.048 Mbps, G.732/733
Line Coding:	B8ZS and AMI for T1 and HDB3 for E1
Framing:	D4, ESF for T1 and PCM30 (Channel Associated Signaling) or PCM31 (Signaling Disabled) for E1
Time Slot Selection:	$n \times 64$ Contiguous or Arbitrary Blocks for Drop and Insert
Data Rates:	64, 128, 192, 256, 320, 384, 512, 640, 768, 960, 1024, 1280, 1536, 1920 Kbps

Environmental

Prime Power:	100 to 240 VAC, 50 to 60 Hz, 1.0 A (IEC 3-Pin Power Connector with Switch)
Operating Temperature:	0 to 50° C, 95% Humidity, Noncondensing
Storage Temperature:	-20 to 70° C, 99% Humidity, Noncondensing

Physical

Chassis Size:	19" x 17" x 1.75" (48.26 x 43.2 x 4.45 cm)
Weight:	8 Pounds (3.6 Kg)
Shipping Weight:	10 Pounds (4.5 Kg)

U.S.A./Canada: 3138 East Elwood Street, Phoenix, Arizona 85034 USA Tel: +(1) 602.437.9620 Fax: +(1) 602.437.4811
6340 Sequence Drive, San Diego, California 92121 USA Tel: +(1) 858.458.1800 Fax: +(1) 858.657.5400

Europe/Middle East/Africa: Charwell House, Wilson Road, Alton, GU34 2PP, United Kingdom Tel: +(44) 1420.540.233 Fax: +(44) 1420.540.232

Latin America: 6340 Sequence Drive, San Diego, California 92121 USA Tel: +(1) 858.458.1800 Fax: +(1) 858.657.5400

China: Room 405, Building B, Heqiao Mansion, No. 8 Guanghua Road, Chaoyang District, Beijing 100026 China Tel: +(86) 10.658.31975 Fax: +(86) 10.658.31974

Asia-Pacific: 15 McCallum Street, #12-04, NatWest Centre, Singapore 069045 Tel: +(65) 6225.4016 Fax: +(65) 6325.1950

Jl M.T. Haryono Kav 25, Jakarta, Indonesia 12820 Tel: +(62) 21.521.3733 Fax: +(62) 21.252.0142

www.radn.com

Prices, specifications, and product availability subject to change without notice. All trademarks acknowledged.

© Copyright 2004 Radyne ComStream Corporation. All rights reserved.

ML-0002C 05/04

